

MAXUM

Next Generation
DC Commercial Door Operator

DATA SHEET

TDC Trolley Operator
SECTION 08 71 13



Key Features

Standard Application

Recommended for door types including:

- Sectional Doors (Standard Lift)
- Standard Duty Cycle and Extended Duty Cycle Applications

Rated Duty Cycle

Standard Duty: Up to 20 cycles per hour and 90 cycles per day
Extended Duty: Up to 30 cycles per hour and 150 cycles per day

Operator Speed

Average 12" per second for Sectional doors

Limit Settings

Electronic limits via Floor Level Wall Controller with LCD display

Emergency Disconnect for Manual Operation

Emergency release

Emergency Disconnect with Auto - Reconnect

Reconnects when door release mechanism is reengaged

Programming

Floor Level Wall Controller with LCD display to program and commission door

Circuit Board

DC Logic Circuit Board

Timer-to-Close

Programming through menu on wall controller. Option is available in B2 Mode with two settings. User can select a desired Timer-to-Close (TTC) time duration under that menu

Mid-Stop

Program setup under System Configuration Operating Mode, Mid-stop

Battery Backup

DC7AH (2): 7 Ah batteries and mounting bracket (optional)

Run Time Protection

Standard Duty: 20 Cycle Count and Cycle 21% within a 60 minute threshold
Extended Duty: 30 Cycle Count and Cycle 37% within a 60 minute threshold

Motor Reverse Action Protection

Stop Fast: 250ms ramp

Stop Ramp: 500ms-2000ms; Stop button while opening

Emergency (Safety-Chain): CTM trigger immediate stop

Motor Operator Wall Controller

Floor Level Wall Controller with LCD screen using 2 wire interface to connect to powerhead

Trolley Track

Dual L-Rail Trolley Track

LiftMaster

MAXUM

Next Generation DC Commercial Door Operator

TDC Trolley Operator

SECTION 08 71 13

DATA SHEET

Specifications:

Radio Receiver	LiftMaster Security+ 2.0
Voltage Connections	120Vac 1 PH/240Vac 1/3PH; 480Vac 3PH; 208Vac 3PH (via transformer); 600Vac 3PH (via transformer)
Accessory Power	24Vdc, 1A Auxiliary Output
Drive Reduction	65:1 Gearbox with #48 Chain Output on 700 units and #41 Chain Output on 1200 and 2200 units
Brake	Electromechanical for operators that support doors up to 700 and 1200 lbs. Brake is included on 2200 models.
Construction	NEMA 1 type electrical box, heavy duty 11 gauge steel frame with durable powder coat finish. NEMA 4X type electrical box for NEMA 4X rated units
Warranty	2 years

Installation Features:

Maximum Door Weight See SKU listing below for maximum door weights allowable by SKU

Connectivity:

Wi-Fi® Connect to Wi-Fi via Connectivity option on the wall controller
Internet Connectivity myQ® technology enables remote monitoring and control via smartphone, tablet, computer. myQ Facility technology enables Diagnostics, absolute cycle count, service cycle count, and remote management

Door Weight Chart

SKU	PRODUCT FAMILY	MAX DOOR WEIGHT
TDC7S1BMC	Trolley	700 lb.
TDC7S4BMC	Trolley	700 lb.
TDC12S1BMC	Trolley	1200 lb.
TDC12S4BMC	Trolley	1200 lb.
TDC12X1BMC	Trolley	1200 lb.
TDC12X4BMC	Trolley	1200 lb.
TDC22X1BMC	Trolley	2200 lb.
TDC22X4BMC	Trolley	2200 lb.
TDC12X1N4XMC	Trolley	1200 lb.
TDC12X4N4XMC	Trolley	1200 lb.
TDC22X1N4XMC	Trolley	2200 lb.
TDC22X4N4XMC	Trolley	2200 lb.

LiftMaster®

MAXUM

Next Generation DC Commercial Door Operator

TDC Trolley Operator

SECTION 08 71 13

Dimensions

	A	B
700 lb. Standard	18.552"	21.065"
1200 lb. Standard	18.867"	21.380"

